

RUSTMASTERS PTY LTD

COMPLETE CORROSION CONTROL

**PO Box J 363 COFFS HARBOUR
NSW 2450**

ph 02 66545422

dick@rustmasters.com.au

Rustmasters Data Sheet

IS11

Issued JULY 06

**Rustmasters®
METALMASTER**

DEFINITION	Rustmasters Metalmaster is a blend of Rustmasters Alucoat and Zinc Phosphates. The ability to penetrate slight rust and adhere to sound metal surface below and seal clean lightly abraded steel providing a tough corrosion resistant ultraviolet - stable coating.
USES	As a sealer on:- Clean Steel Lightly rusted steel Weathered galvanised steel Aluminium
PREPARATION	Area to be degreased, mill scale must be removed. Basic preparation on rusted steel is as Rustmasters PDS. Aluminium must be abraded to provide a suitable surface.
APPLICATION	Mix thoroughly before use, Application by brush - roller - airless or conventional spray methods. On rusted steel use Rustmasters Rust Sealer as a base (sealer) coat, then apply Metalmaster wet on wet for best results.
COVERAGE	12 to 15 m ² /ltr
DYING TIME	Touch dry 1 hour @ 25 ⁰ C Hard dry 6hours @ 25 ⁰ C
THINNING	Not required.
CLEAN UP	White Spirits or Mineral Turpentine
OTHER USES	As a top coat over Rustmasters Rust Sealer where a hard wearing system is required.

This information is based on data believed by Rustmasters Pty Ltd to be accurate at the time of writing but subject to change without notice. It is given in good faith but no warranty expressed or implied is made concerning its detailed accuracy, completeness or otherwise. Independent determination as to the suitability of the product, by the user, should be made to ensure its correct application and use. We have no control over the conditions under which this product is stored, handled or used, therefore our recommendations must not be regarded as amounting to legal warranty or as involving any liability on us.